

Genelite

GH2000



PORTABLE POWER

POWERED by
HONDA™

mecc alte spa

Technical

Model	GH 2000
Type	Portable
Speed	3000 RPM
Phase/Voltage	1/240
Frequency	50 Hz
Max power kW	2.2kW
Continuous Output	2.5kVA
Noise Level (dBA @ 7m)	72
Frame	Small roll frame

Engine

Manufacturer	Honda
Engine Model	GX160
Type	O.H.V.
Starting	Recoil start
Fuel	Unleaded Petrol
Run Time	3.1hr @ 100%, 5hrs @ 60% Load
Consumption	1.2 L/h
Tank Capacity	3.6 L
HP 3000 rpm Continuous	3.4
Cubic Capacity	163 Cm3
Oil Capacity	0.6 L

Alternator

Alternator Brand	Meccalte
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Outlets

Outlet	2 x 10amp switched with thermal overload
---------------	--

Dimensions & Weight

Length	67 Cm
Width	44 Cm
Height	48 Cm
Weight	33 Kg

Options

Outlets	Weather protected IP33 & Weatherproof IP66
Protection	RCD/ELCB IP30 or IP66
Long Range Tank	15 Litre Capacity