

GH5000E



PORTABLE POWER

Technical

Model GH 5000E Portable Type 3000 RPM Speed Phase/Voltage 1/240 50 Hz Frequency Max power kW 5.0kW **Continuous Output** 6.0kVA Noise Level (dBA @ 7m) 72

Frame Large roll frame

Engine

ManufacturerHondaEngine ModelGX340TypeO.H.V.

Starting Recoil & Electric start
Fuel Unleaded Petrol

Run Time 3.0 hr @ 100%, 4.2hrs @60%

Tank Capacity 6.1 L
HP 3000 rpm cont 7.2 HP
Cubic Capacity 337 Cm3
Oil Capacity 1.1 L

Alternator

Alternator Brand Meccalte
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Outlets

Outlet 10amp + 15amp switched with thermal overload

Dimensions & Weight

 Length
 85 Cm

 Width
 57 Cm

 Height
 60 Cm

 Weight
 58 Kg

Options

Outlets Weather protected IP33 & Weatherproof IP66

Protection RCD/ELCB IP30 or IP66
Wheel kits Two wheel or four wheel
Frames Extra large Roll Frames

Alternators Oversized, Single or Three Phase

Long Range Tank 15 Litre Capacity

