



GH8000E-3



PORTABLE POWER

POWERED by
HONDA™

mecc alte spa

Technical

| | |
|-------------------------------|------------------------|
| Model | GH 8000E-3 |
| Type | Portable |
| Speed | 3000 RPM |
| Phase/Voltage | 3 / 240-415 |
| Frequency | 50 Hz |
| Max power kW | 8.0 kW |
| Continuous Output | 9.0 kVA |
| Noise Level (dBA @ 7m) | 72 |
| Frame | Extra Large roll frame |

Engine

| | |
|-------------------------|-----------------------------|
| Manufacturer | Honda |
| Engine Model | iGX440 |
| Type | O.H.V. |
| Starting | Recoil / Electric start |
| Fuel | Unleaded Petrol |
| Run Time | 1.97 hr @ 100%, 2.8hrs @60% |
| Tank Capacity | 5.9 L |
| HP 3000 rpm cont | 10.1 HP |
| Cubic Capacity | 438 Cm3 |
| Oil Capacity | 1.1 L |

Alternator

| | |
|----------------------------|--------------|
| Alternator Brand | Meccalte |
| Type | Brushless |
| Harmonic Distortion | Less than 5% |
| Protection Class | IP 23 |
| Insulation Class | Class H |

Outlets

| | |
|---------------|--------------------------------------|
| Outlet | 20amp 5pin IP66 with circuit breaker |
|---------------|--------------------------------------|

Dimensions & Weight

| | |
|---------------|-------|
| Length | 86 Cm |
| Width | 50 Cm |
| Height | 57 Cm |
| Weight | 80 Kg |

Options

| | |
|------------------------|--|
| Outlets | Weather protected IP33 & Weatherproof IP66 |
| Protection | RCD/ELCB IP30 or IP66 |
| Wheel kits | Two wheel or four wheel |
| Frames | Extra large Roll Frames |
| Alternators | Oversized, Single or Three Phase |
| Long Range Tank | 15 Litre Capacity |